



**US Army Corps
of Engineers**

Hydrologic Engineering Center

Flood Damage Assessments Using Spatial Data Management Techniques

May 1978

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.

1. REPORT DATE (DD-MM-YYYY) May 1978		2. REPORT TYPE Technical Paper		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Flood Damage Assessments Using Spatial Data Management Techniques			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Darryl W. Davis, R. Pat Webb			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Corps of Engineers Institute for Water Resources Hydrologic Engineering Center (HEC) 609 Second Street Davis, CA 95616-4687				8. PERFORMING ORGANIZATION REPORT NUMBER TP-57	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/ MONITOR'S ACRONYM(S)	
				11. SPONSOR/ MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES Presented at the Symposium on Watershed Management, Rice University, Mary 1978.					
14. ABSTRACT The Corps of Engineers Hydrologic Engineering Center has developed techniques that perform the spatial data analysis approach and individual structure approach and work is near completion on an integrated analysis package. The capability therefore exists to perform damage appraisals in a manner that encourages a general geographic and land use should the need arise. This paper discusses the basic concepts of a spatial data management approach to damage appraisals and highlight(s) its integrated use with more traditional individual structure approaches. Selected example results are presented.					
15. SUBJECT TERMS spatial data, flood damage analysis, flood benefit analysis, grid databases					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 34	19a. NAME OF RESPONSIBLE PERSON
a. REPORT U	b. ABSTRACT U	c. THIS PAGE U			19b. TELEPHONE NUMBER

Flood Damage Assessments Using Spatial Data Management Techniques

May 1978

US Army Corps of Engineers
Institute for Water Resources
Hydrologic Engineering Center
609 Second Street
Davis, CA 95616

(530) 756-1104
(530) 756-8250 FAX
www.hec.usace.army.mil

TP-57

Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution with the Corps of Engineers.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

FLOOD DAMAGE ASSESSMENTS USING SPATIAL DATA MANAGEMENT TECHNIQUES^{1/}

by

Darryl W. Davis ^{2/} and R. Pat Webb ^{2/}

INTRODUCTION

Modern damage appraisals serve the joint tasks of estimating existing damage potential and providing the bases for formulation and evaluation of a range of management actions expected to perform under alternative future development patterns and land use management policies. Spatial data management techniques in which land use, topographic and other natural resource information is catalogued into computerized data files offers substantial potential for performing comprehensive flood damage analysis to meet these needs. The strength of the techniques are the geographic and land use orientation that must be adopted to apply the methods and the significant opportunity to quantitatively assess land use development patterns and policies.

In most flood plains, several unique activities that may collectively involve one or more structures do not fall into logically defined land use or damage potential categories. These may be major industries, unique commercial properties, or religious and service groups. Cataloguing and

^{1/} Presented at the Symposium on Urban Watershed Management, 25-26 May 1978, Rice University.

^{2/} Chief, Planning Analysis Branch and Environmental Resources Planner, Planning Analysis Branch, the Hydrologic Engineering Center, Davis, CA.

managing the damage potential of these structures individually seems appropriate to maintain credibility in the analysis.

The Corps of Engineers Hydrologic Engineering Center has developed techniques that perform the spatial data analysis approach and individual structure approach and work is near completion on an integrated analysis package. The capability therefore exists to perform damage appraisals in a manner that encourages a general geographic and land use approach (thus greatly facilitating the study of nonstructural measures) while preserving the ability to analyze individual, unique structures should the need arise.

This paper discusses the basic concepts of a spatial data management approach to damage appraisals and highlight(s) its integrated use with more traditional individual structure approaches. Selected example results are presented.

FLOOD DAMAGE ASSESSMENT CONCEPTS

Flood damage assessments are performed to provide quantitative information on the social cost of flooding and to provide a sound basis for formulating, evaluating and implementing a range of remedial management actions. Flood damage potential assessments of existing flood plain development provide the basis for identifying critical problem areas and for development of actuarial insurance premiums for government and private industry. Damage appraisals performed in the aftermath of flood events provide the data used as the basis for the efficient and equitable allocation of relief funds and other emergency assistance. Damage estimates of potential future development scenarios can encourage local government agencies and private


individuals to make wise land use decisions considering the flood hazard consequences. Several types of analysis' for a range of development conditions and careful segmenting of damageable areas' are required to meet these information needs.

The two major types of damage appraisals performed to supply these information needs are 1) "event" analysis (often referred to as single event damage), and 2) expected annual damage analysis (often referred to as average annual damage). The damage assessments for both types involve technical procedures to develop and make coordinated use of economic (damage), hydrologic, and hydraulic data.

The single event analysis includes development of a damage potential function (elevation-damage curve), and hydrologic data (perhaps only stage) for the event of interest. The damage for the event is simply "read out" for the flood level of interest.

The expected annual damage analysis requires the additional development of exceedance frequency information which is used to perform the probability weighting. This could include a stage-exceedance frequency function directly or more commonly, the development of a flow-exceedance frequency function (commonly referred to as a frequency curve) and an elevation-flow curve (commonly referred to as a rating curve).

Figure 1, Damage Computation Concepts (Hydrologic Engineering Center, June, 1977) reproduced here summarizes the functional relationships and their respective role in damage appraisal studies directed toward computing the expected annual damage. The final step in the appraisal is conceptually illustrated by the hatching of the Damage-Frequency relationship. The



The basic functional evaluation relationships and the derived relationships are shown above and how they are constructed is described herein.

Stage-Flow Relationship: This is a basic hydraulic function that expresses, for a specific location, the relationship between flow rate and stage and is frequently referred to as a 'rating curve.' It is usually derived from water surface profile computations.

Stage-Damage Relationship: This is the economic counterpart to the stage-flow function and represents, at a specific location, the damages which will occur in a river reach at various river stages. Usually the damage represents an aggregate of damage which occur some distance upstream and downstream from the specified location. It is usually developed from field damage surveys.

Flow-Frequency Relationship: This defines the relationship between exceedance frequency and of annual peak flow at a location. It is the basic function describing the probability nature of stream flow and is commonly determined from either statistical analysis of gaged flow data or through watershed model calculations.

Damage-Frequency Relationship: This relationship is derived by combining the previously discussed basic relationships using the common parameters stage and flow. For example, the damage for a specific exceedance frequency is determined by ascertaining the corresponding flow rate from the flow-frequency function, the corresponding stage from the stage-flow function and finally the corresponding damage from the stage-damage relationship. Any changes which occur in the stage-damage, stage-flow or flow-frequency function because of watershed, development or flood plain management measure implementation will be reflected in the damage-frequency function and therefore the magnitude of the expected annual damage computed as the integral (area underneath) the function.

Other Functional Relationships: The flow-damage relationship is developed by combining the stage-damage with the stage-flow relationship using stage as the common parameter. The stage-frequency relationship is developed by combining the stage-flow with the flow-frequency relationship using flow as the common parameter. The damage-frequency relationship could then be developed as a further combination of these derived relationships.

Figure 1

expected value is the probability weighted value and is shown as the area under the curve. This is exactly identical to computing the mathematical expectation of a cumulative distribution function. As would be expected, present day analysis is often computerized so that the integration to compute the expected value is performed by numerical methods.

Flood plain areas for which damage appraisals are performed normally encompass rather extensive stream reaches in which there can be significant changes in the basic evaluation functions from one location to another. It is common practice to subdivide the damageable area into "damage reaches" for which a unique set of the functional relationships is developed. Criterion for determining the geographic extent of the reaches includes a) reasonably uniform hydraulic response (parallel water surface profiles for the range of flows which are significant to the calculation of expected annual damages), b) a constant flow regime (no significant flow changes, such as tributaries, encompasses), c) political, economic and other aggregation units of interest preserved and d) allowance for accurate analysis of the range of management actions that might be investigated. As an example, a study area such as the vicinity of Athens, Georgia (200 square miles) might be partitioned into 70 to 80 damage reaches, each of which would have the unique evaluation functions of a damage curve, an exceedance frequency curve, and a rating curve prepared.

The individual functions may be developed by several alternative means. The text in Figure 1 suggests a few. The damage potential function is singled out for discussion and analysis in this paper because it is the primary

mechanism for quantifying the direct effect of flood plain management actions intended to be applied to both existing and future development patterns.

DEVELOPMENT OF DAMAGE POTENTIAL FUNCTIONS

The most direct and complete approach to development of damage functions for present flood plain development would be to perform a complete exhaustive inventory of the structures and terrain in the flood plain. This would include surveying the ground floor elevation of all structures and examination of each structure and its contents to determine the damage potential. Several other approaches from this exhaustive inventory to structure and terrain generalization (the spatial approach) are briefly discussed below.

A less intense inventory approach could be to approach the task as a structure inventory, but to classify and generalize the types of structures and their damage potential. Structures are thus grouped and inventorying proceeds basically to catalogue terrain and structure/contents type. This is a common approach for damage function development for flood plains with a manageable number of structures. A more statistically based approach used increasingly more often in recent years, would be to stratify the flood plain development by damage potential, then sample the stratified categories applying principles of statistical sampling theory. The stratification would probably be by structure type, flood potential, structure value, and terrain. Note that not all structures would be catalogued and analyzed - only those "sampled". After the stratified sample has been analyzed, the damage potential for the entire study area is projected. Further generalization of damage function construction is possible by "zoning" the flood

plain into homogeneous areas of damage potential (say common structure types and common elevation). This latter is a common approach that moves away from individual structures into a more general land use approach.

The spatial data management approach has characteristics of most of the above approaches integrated into its method. Flood plain occupancy is determined by grouping development into land use categories, damage potential is determined by sampling structure types and values within the land use categories to develop composite damage functions, and the terrain variation is preserved by gridding the stream reaches and assigning elevations to the grids. The size of the grid that should be used is a function of the terrain and land use variation. To date most studies use 1.148 acre grids although a range of 0.18 - 4.5 acres has been employed in other studies. The approach has been devised so that all data are locationally accurate (referred to as having spatial integrity) and thus the method is computerized and directly linked to modern geographic analysis concepts. The approach therefore has a significant land use focus and is easily applied to the study of land use management policies and nonstructural flood plain management alternatives. An important concept central to the spatial approach to damage appraisals is the grid cell data bank (the gridded geographic data file).

GRID CELL DATA BANK

A grid cell data bank is a stored computer file of spatial data (map type data) which can be accessed and processed for a variety of analyses. "Guide Manual for the Creation of Grid Cell Data Banks" (Hydrologic Engineering Center, June 1978), contains detailed guidance on the creation of

data banks. The stored data bank is the central feature of damage appraisals using spatial data management techniques.


Spatial data occurs both as discrete forms that can be bounded by definite lines (e.g. land use, damage reaches, etc.) and as continuously changing data (e.g. topographic elevation). Discrete types of data may be classified into groups and legended, while continuous data can be assigned a representative value for each specific grid (e.g. topographic elevation for each grid).

The location of each cell and the value (legend) for each variable must be recorded. This is accomplished by cataloguing each grid cell with a specific location (row and column) as the first two values for a grid cell record. All data associated with a particular grid cell is then stored sequentially at the address specified for that grid cell. The stored data bank exists as a matrix of numbers which identify data values and location.

Part a of Figure 2, Grid Cell Data Bank Concepts, illustrates conceptually how a single data variable may be visualized as a numerical matrix with the three dimensions of row, column and data value for each grid cell. Figure 2b illustrates conceptually a portion of a grid cell data bank containing several data variables. Grid data stored to represent several variables is referred to as a multivariable file.

The specific data variables and their characteristics that must be placed in a gridded data base, together with the procedures for processing to perform damage appraisals are discussed in subsequent paragraphs.

a. Single Variable



b. Multiple Variables

	1	2	3	4	5	6	7	8	9	10
1	1	1	1	1	6	6	6	6	6	6
2	1	1	1	1	6	6	6	6	6	6
3	4	4	4	4	4	4	6	6	6	6
4	4	4	4	4	4	4	6	6	6	6
5	4	4	4	4	4	4	7	7	7	7
6	4	4	4	4	4	4	7	7	7	7
7	4	4	4	4	4	4	7	7	7	7

Existing Land Use (Data Variable 4)
 Code 1 - Single Family Housing
 Code 4 - Industrial
 etc.

	1	2	3	4	5	6	7	8	9	10
1				2	2	2				
2				2	2	2				
3				2	2	2				
4				2	2	2	3	3		
5				2	2	2	3	3		
6				3	3	3	3	3		
7				3	3	3	3	3		

Damage Reach (Data Variable 6)
 Code 2 - Damage Reach 2
 Code 3 - Damage Reach 3

	1	2	3	4	5	6	7	8	9	10
1				20	20	20				
2				21	21					
3				21	21	21				
4				22	22	22	22	23		
5				23	23	23				
6				24	24	24	25			
7				24	24	25	25	25		

Reference Flood (Data Variable m)
 Code 20...25 - Reference Flood
 Elevation in feet

Figure 2.

GRID CELL

DATA BANK CONCEPTS

DAMAGE FUNCTIONS USING SPATIAL DATA APPROACH

Overview

The spatial data management technique for generating elevation-damage functions adapts traditional methods to the grid cell data bank concept. The methodology consists of constructing a unique elevation-damage relationship for each grid cell within the flood plain (based on topographic ground elevation, land use, and composite damage function assigned to the grid cell) and aggregating all of the grid cells assigned to a particular damage reach to each appropriate index location using a reference flood as the mechanism for adjusting for a sloping water surface profile (Hydrologic Engineering Center, 1975).

Damage Reaches

Damage reach boundaries are determined based on the traditional procedure that includes determining reaches with consistent parallel water surface profiles for the range of discharges which are significant to the calculation of expected annual damages while maintaining the economic detail desired for analysis. The damage reach boundaries are encoded and processed into the grid cell data bank with each cell within a reach assigned the reach identification value. The damage reach identification is used to aggregate grid cells to the appropriate damage reach index location.

Reference Flood

Since flood profiles result in different water surface elevations throughout a damage reach, a reference flood is used as a device to properly adjust the elevation for aggregation purposes, of each cell within the reach



with respect to the index location, Each cell is assigned a reference flood water surface elevation which is used with the reference flood elevation at the index location to adjust the composite damage function for proper aggregation of damages at the index location. A schematic of this process is shown in Figure 3, Damage Function Development (Hydrologic Engineering Center, 1975).

The reference flood placed in the data bank is a flood within the range which is critical for flood damage computation, usually a mid-range flood is selected to be a 25 to 50 year exceedance interval event. In studies that will examine flood plain management policies, it is useful to use an accurate 100 year profile as the reference flood. The reference flood elevations should be determined from detailed water surface profile analysis. If water surface profiles are not available, the slope of the flood profile through a damage reach may be crudely approximated by the slope of the thalweg (channel bottom) of the main stream or the slope of the adjacent flood plain itself.

Composite Damage Function

A composite damage function is defined as a stage-damage function for a unit area of a specific land use category that has significant damage potential. These functions may be developed by averaging the structural and related content values obtained from sampling a range of structure values and types within each land use category by use of field surveys, or by the review of tax records and interviews conducted with regional and local agencies, or other traditional field survey methods. The composite damage function may include direct and indirect damages that are associated with each particular

DATA REQUIRED



INDEX LOCATION DAMAGE FUNCTION CONSTRUCTION

STEP 1, Develop Elevation - damage Function at Each Cell

- Determine land use from grid file
- Retrieve appropriate composite stage damage function
- Determine grid elevation of cell from grid file
- Tabulate elevation-damage for cell from above

STEP 2, Aggregate Cells to Index Location

- Determine cell damage reach assignment
- Determine index location reference flood elevation (X_1)
- Determine cell reference flood elevation (X_2)
- Adjust cell elevation-damage function by $(X_2 - X_1)$
- Aggregate cell adjusted elevation-damage function at index station
- Repeat for all grid cells

DAMAGE FUNCTION DEVELOPMENT

land use category. Table 1, Composite Damage Function for Low Density Residential Land Use Category, illustrates an example of a composite stage-damage function of a land use category. A function is developed for each land use category of interest in the investigation.

Aggregate Damage Function

The flood damage associated with each grid cell is determined by matching the land use for each grid cell with the appropriate composite damage function (in effect placement of the function on the elevation assigned to the cell). The individual cell elevation-damage functions are then aggregated to the appropriate index location by use of the mechanism of the reference flood. A schematic of this procedure is shown in Figure 3, referred to previously. The computer program DAMCAL that performs the aggregation may also be used to develop the composite damage function. The following types of information are used in developing the composite stage-damage function for a specific land use category.

- . stage vs % damage for structure
- . stage vs % damage for contents
- . value of structure
- . value of contents (option available - % of structure value)
- . indirect damage (option available - dollar amount or % structure and contents)
- . development density (number of structures per grid cell)
- . vacancy allowance (the proportion of land classified in the particular category that is in fact developed)

Table 1
EXAMPLE COMPOSITE DAMAGE FUNCTION

HIGH DENSITY RESIDENTIAL

```

*****
* DEPTH * PER CENT * PER CENT * AMOUNT OF DAMAGE *
* OF * DAMAGE * DAMAGE * PER GRID CELL *
* WATER * STRUCTURE* CONTENTS *IN THOUSAND DOLLARS*
*****
*
* -2.00 * 0.00 * 0.00 * 0.00 *
*
* -1.00 * 4.70 * 1.80 * 5.07 *
*
* .10 * 13.30 * 13.60 * 17.28 *
*
* 1.00 * 17.70 * 46.40 * 32.80 *
*
* 2.00 * 20.70 * 64.50 * 41.91 *
*
* 3.00 * 24.00 * 76.40 * 49.15 *
*
* 4.00 * 27.00 * 84.50 * 54.79 *
*
* 5.00 * 31.00 * 88.20 * 59.86 *
*
* 6.00 * 34.00 * 92.70 * 64.25 *
*
* 7.00 * 38.30 * 93.60 * 68.63 *
*
* 8.00 * 42.30 * 95.50 * 73.06 *
*
* 9.00 * 48.70 * 95.50 * 79.11 *
*
* 10.00 * 57.70 * 95.50 * 87.62 *
*
*****

```

DENSITY OF THE LAND USE UNITS PER GRID CELL = 4.00

BASE VALUE OF THE STRUCTURE = 30000.00

BASE VALUE OF THE CONTENTS = 11000.00

VACANCY FACTOR (PER CENT DEVELOPED) = 75.0

INDIRECT DAMAGES IS 5.00 PERCENT OF THE TOTAL

The data is prepared by land use category and DAMCAL accesses the grid data file and computes elevation-damage relations for all pertinent land use categories and damage reaches

Once the composite damage function has been developed for the land use pattern of interest, the function can be easily adjusted to reflect each specified flood plain management alternative measure and the corresponding performance criteria that are of interest in plan formulation. The capability to automatically adjust these functions is provided by DAMCAL.

Land Use

Land use concepts are a significant aspect of the spatial approach to damage appraisal. The care with which categories are chosen, and classification performed to a great degree control the accuracy of the results. Nomination of large numbers of categories (more than 20) can result in an apparent improvement in accuracy for existing development, but greatly complicate assessment of futures (its hard enough to forecast 3-5 categories, much less 20 or more). Also, averaging does have some virtues - today's flood plain development is one sample in time, it will likely change somewhat within existing buildings. Overemphasizing the detail of present use can lead one away from the central concept of all flood plain management actions - preventing damage in the future. Clearly a balance must be struck between adequate capturing of variation within and among use types, and prudence in use of investigation resources. While much is yet to be learned, it does appear that an upper practical bound in land use categories for damage analysis purposes is in the range of 15 to 20.

Example Results

Expected annual damage calculations require that the aggregate damage functions be merged with the rating curve and the flow exceedance frequency curve that have been derived by conventional or other means for the index location. In recent pilot studies for expanded flood plain information studies, the computer program HEC-1 (Hydrologic Engineering Center, 1975) was used to coordinate the data and perform the computations. The data transfer and coordination tasks were automated for that application. Other traditional damage calculation programs could be used equally as effectively.

Table 2, Summary Damage Evaluations (Davis, 1978) summarizes selected expected annual damage assessments for a range of watershed conditions and land use control policy sets for damage reaches within the Trail Creek watershed, a 12 mi.² tributary to the Oconee River in Athens, Georgia, selected to test the techniques.

The results are somewhat surprising and at first glance may be difficult to understand. An initial reaction might be that evaluation condition CODE IV should be similar to CODE I since the policy of no new development occurring at elevations below the 100-year event is in effect. The table shows a large increase in expected annual damages. This increase is because (1) damage does occur for new basement construction, (2) the 100-year flood for 1990 land use conditions is higher than the 100-year flood for existing land use conditions thereby increasing damage to existing development, and (3) damage is sustained by new development from events that exceed the 100-year event. Several other evaluations that include a number of alternative control and flood proofing policies are included to demonstrate the broad capability

TABLE 2
 SUMMARY DAMAGE EVALUATIONS
 (Expected Annual Damage in 1000's \$)

CODE	EVALUATION CONDITION		DAMAGE REACH			TOTAL
	LAND USE POLICY ^{1/}	HYDROLOGY	1	2	3	
I	Existing	(1975) Existing	1.5	1.9	11.9	15.3
X	1990 with no development controls	1990	1033.3	350.0	32.7	1416.0
IV	1990 with new develop- ment at 1975 100-year flood level	1990	19.3	63.8	23.8	106.9
V	1990 w/new devel. @ 1975 100-year and flood proofed to ground floor	1990	16.8	18.9	4.7	40.4
VIII	1990 w/new devel. @ 1990 100-year and flood proofed to ground floor	1990	11.9	16.0	2.8	30.7

^{1/} The 1990 land use condition is a projection based on local agency judgement. In some instances, such as Damage Reach #3, 1990 urban type development has displaced several acres that are presently agricultural.

of the spatial data management technique as well as present some interesting evaluations of policies designed to manage flood losses. The capabilities of the spatial data management technique for evaluating a range of nonstructural flood plain management measures is described by (Webb and Burnham, 1976).

Significant Characteristics

Several significant characteristics of flood damage appraisals using spatial data management techniques are important to emphasize.

- a) The approach emphasizes a land use focus in damage assessments.
- b) It is technologically sensitive and responsive to policy analysis.
- c) It is by nature highly computerized and amenable to automated analysis.
- d) A high quality gridded data base is required to assure the fidelity of the results.
- e) The overall technique and investigative environment in which it is operable encourages a geographic approach to flood plain management.
- f) The focus is moved away from specific (and perhaps unique and important in some instances) structures as the basis for assessment.

UNIQUE STRUCTURE INVENTORY

The land use focus, while significantly advancing flood plain management ideals in most respects, can result in loss of important detail and thus credibility when attempting to make definitive estimates for existing flood plain development within which there may exist single, isolated unique structures. Such structures could be industrial complexes, specialty commercial enterprises, churches, historic buildings and the like.

To accommodate this need, a specific structure inventory computer program (STRUCTURE INVENTORY) was developed during the comprehensive pilot studies that had the following features

- . Provides a computerized structure inventory capability,
- . Adaptable as a complete or partial (supplement to) alternative to the spatial approach,
- . Capable of systematically managing data on unique damage potential and value for structures,
- . Compatible with spatial data files so that aggregation, policy analysis, and data file integration can be performed.

The basic concept of automating a structure inventory is not new in principle or practice. However, the careful construction of the data handling features, such that STRUCTURE INVENTORY files are compatible with spatial gridded data files and sensitive to policy analysis, is quite unique. In effect, the basic groundwork was laid for the subsequent integrated analysis using spatial and unique structure data that is described later.

Figure 4, Damage Survey Field Form, was designed to systematize the field data collection task for the structure inventory program and can serve as a vehicle to describe the specific features of the capability. Note that data are needed for the REACH, 1st FLOOR ELEV, REF FLOOD ELEV, and BASEMAP ROW and COLUMN all in upper right corner of the form. These are the same data used in the spatial approach and may be recorded directly upon the form, if available, or if the coordinates (row and column) are recorded, these data can be automatically retrieved from the grid cell data

STUDY _____
 DATE _____
 PREPARED BY _____

DAMAGE SURVEY FIELD FORM

DRAFT 3/77
RPW-HEC

REACH _____
 BLDG ID _____
 1st FLOOR ELEV _____
 REF FLOOD ELEV _____
 RIVER MILE _____
 BASEMAP ROW _____ COLUMN _____

ADDRESS _____
 BLDG SIZE _____ STRUCTURE & MATERIAL TYPE _____

LAND USE CATEGORIES

REMARKS _____

LOCATION	DAMAGE TYPE	VALUE	DAMAGE FUNCTION
FIRST FLOOR	STRUCTURE (1FS)		
	CONTENTS (1FC)		
	OTHER (1FO)		
BASEMENT	STRUCTURE (BS)		
	CONTENTS (BC)		
	OTHER (BO)		
ABOVE FIRST FLOOR	STRUCTURE (AS)		
	CONTENTS (AC)		
	OTHER (AO)		

BUILDING TYPE FOR DAMAGE CALCULATION PURPOSES

1. FIRST FLOOR ONLY OR COMPOSITE
2. FIRST FLOOR AND BASEMENT
3. FIRST FLOOR AND FLOORS ABOVE
4. THE WORKS (BASEMENT, FIRST FLOOR, AND ABOVE)

FIRST CARD

REACH	BLDG ID								ROW	COLUMN							LAND USE								1ST FLOOR ELEV.								REF FLOOD ELEV.								BUILDING'S DAMAGE TYPE FUNCTION			
1	2	3	4	5	6	7	8	9	10	1	2	3	4	5	6	7	8	9	20	1	2	3	4	5	6	7	8	9	30	1	2	3	4	5	6	7	8	9	40					
								1																																				

1FS VALUE										BC DMGE FUNCTION	1FC VALUE										FO DMGE FUNCTION	1FO VALUE										BS DMGE FUNCTION	BS VALUE										BLANK	
41	2	3	4	5	6	7	8	9	50	1	2	3	4	5	6	7	8	9	60	1	2	3	4	5	6	7	8	9	70	1	2	3	4	5	6	7	8	9	80					

SECOND CARD

REACH	BLDG ID								BC DMGE FUNCTION	BC VALUE										BO DMGE FUNCTION	BO VALUE										AS DMGE FUNCTION	AS VALUE										AC DMGE FUNCTION	
1	2	3	4	5	6	7	8	9	10	1	2	3	4	5	6	7	8	9	20	1	2	3	4	5	6	7	8	9	30	1	2	3	4	5	6	7	8	9	40	41			
								2																																			

AC VALUE										AO DMGE FUNCTION	AO VALUE										ADDRESS																					
42	3	4	5	6	7	8	9	50	1	2	3	4	5	6	7	8	9	60	1	2	3	4	5	6	7	8	9	70	1	2	3	4	5	6	7	8	9	80				

bank. It is possible to specify a set of unique generalized damage functions for the basement, first floor, and subsequent floors if desired, and separate values for each if appropriate. The actual dollar estimates of damage by stage may be directly input if desired. Note also that a land use assignment may be made. This is so that aggregations may be performed and the results be compatible with the spatial approach.

The STRUCTURE INVENTORY program accepts data from the field coded forms and creates a structure file. Other options can then be exercised to aggregate data to index locations, group and count structures, and form aggregate damage functions for nonstructural alternatives such as selective flood proofing, evacuation, partial warning, etc. The file is created such that it may interface with the gridded file, should that prove advantageous.

INTEGRATED SPATIAL AND INVENTORY APPROACH

The observation that an extremely powerful data management approach would be created if the advantages of both the gridded spatial technique and structure inventory were capitalized upon led to the initiation of the development of an integrated analysis capability. The objectives of the integrated approach were defined as:

- . Integrate data management and processing to exploit the respective strengths of each approach,
- . Coordinate data needs between approaches so that businesslike field work could service both,
- . Prepare computer code so that input and output products are

compatible between programs and both ultimately service the comprehensive processing programs that are subsequently used,

- . Preserve, and to the extent possible, enhance the policy flexibility and sensitivity of the respective analyses.

The strategy to accomplish the integrated analysis is based upon preservation of the independence of the spatial and inventory processing programs so that they could be used independently when appropriate. A utility program is being developed that will form the processing interface between the two programs and the data base. This program will scan the data file of inventoried structures to identify the coordinates of cells containing specially catalogued structures, access the grid cell data bank and flag those cells identified so that processing by the spatial program DAMCAL can be adjusted to prevent double counting, and retrieve from the grid file such data as may be missing in the structure file, such as reference flood or ground elevation. The program would then, after aggregate function construction by each separate program, merge the results into a single aggregate file for subsequent analysis in a business-as-usual fashion by other analysis programs such as HEC-1, or by hand for that matter.

PROGRAM STATUS AND AVAILABILITY

Grid Cell Data Bank Creation

The paper presented earlier in this Symposium by Webb and Smith, "...Variables Are NOT Created Equal", describes the present attitude of Corps of Engineers practitioners on creation of data banks. A manual (Hydrologic Engineering Center, 1978) has recently been issued describing

guidelines for creating grid cell data banks and catalogues the computer software necessary to perform the task efficiently and lists where each program may be obtained.

DAMCAL - Spatial Processing Program for Damage Functions

This program was originally developed for the first Corps of Engineers pilot Expanded Scope Flood Plain Study in 1975, and has undergone steady refinement and improvement since then. It has been applied in several studies in the production mode. Final documentation and computer code clean up are nearing completion so that it will be available for public release in mid to late summer 1978.

STRUCTURE INVENTORY

This program was developed in late 1977 to service the Rowlett Creek study reported on in this symposium by Lovell and Smith. The program was successfully tested on a portion of the Rowlett Creek study area and additional testing and application is anticipated in the coming months. It is expected that the program will be prepared for public release late in 1978 or early in 1979. Informal copies of computer code and user documentation may be obtained from the Hydrologic Engineering Center.

Integrated Spatial and Inventory Analysis

Modifications to the basic spatial and inventory programs has been initiated. The utility program that will perform the interface and integration is presently in the active development category. It is expected that the integrated package will be available for applications in late 1978 and ready for public release in mid to late 1979.

SUMMARY AND CONCLUSIONS

Concepts and implementing computer programs have been developed that provide for damage appraisals using modern techniques of spatial data management. The applications to date confirm the soundness of the approach and suggest the methods promise to aide in continuing the important movement toward a geographic approach to flood plain management.

LITERATURE CITED

Davis, D.W., Comprehensive Flood Plain Studies Using Spatial Data Management Techniques. Journal of the American Water Resources Association, June 1978, pp. 587-604.

The Hydrologic Engineering Center, Expected Annual Damage Computations, June 1977.

The Hydrologic Engineering Center, Guide Manual for the Creation of Grid Cell Data Banks, June 1978.

The Hydrologic Engineering Center, Phase I Oconee Basin Pilot Study, Trail Creek Test, September, 1975.

Webb, R.P., and Burnham, M.W., Spatial Data Analysis of Nonstructural Measures, Symposium on Inland Waterways for Navigation, Flood Control and Water Diversions, ASCE, August 1976.

Technical Paper Series

TP-1	Use of Interrelated Records to Simulate Streamflow	TP-39	A Method for Analyzing Effects of Dam Failures in Design Studies
TP-2	Optimization Techniques for Hydrologic Engineering	TP-40	Storm Drainage and Urban Region Flood Control Planning
TP-3	Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs	TP-41	HEC-5C, A Simulation Model for System Formulation and Evaluation
TP-4	Functional Evaluation of a Water Resources System	TP-42	Optimal Sizing of Urban Flood Control Systems
TP-5	Streamflow Synthesis for Ungaged Rivers	TP-43	Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems
TP-6	Simulation of Daily Streamflow	TP-44	Sizing Flood Control Reservoir Systems by System Analysis
TP-7	Pilot Study for Storage Requirements for Low Flow Augmentation	TP-45	Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin
TP-8	Worth of Streamflow Data for Project Design - A Pilot Study	TP-46	Spatial Data Analysis of Nonstructural Measures
TP-9	Economic Evaluation of Reservoir System Accomplishments	TP-47	Comprehensive Flood Plain Studies Using Spatial Data Management Techniques
TP-10	Hydrologic Simulation in Water-Yield Analysis	TP-48	Direct Runoff Hydrograph Parameters Versus Urbanization
TP-11	Survey of Programs for Water Surface Profiles	TP-49	Experience of HEC in Disseminating Information on Hydrological Models
TP-12	Hypothetical Flood Computation for a Stream System	TP-50	Effects of Dam Removal: An Approach to Sedimentation
TP-13	Maximum Utilization of Scarce Data in Hydrologic Design	TP-51	Design of Flood Control Improvements by Systems Analysis: A Case Study
TP-14	Techniques for Evaluating Long-Term Reservoir Yields	TP-52	Potential Use of Digital Computer Ground Water Models
TP-15	Hydrostatistics - Principles of Application	TP-53	Development of Generalized Free Surface Flow Models Using Finite Element Techniques
TP-16	A Hydrologic Water Resource System Modeling Techniques	TP-54	Adjustment of Peak Discharge Rates for Urbanization
TP-17	Hydrologic Engineering Techniques for Regional Water Resources Planning	TP-55	The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers
TP-18	Estimating Monthly Streamflows Within a Region	TP-56	Experiences of the Hydrologic Engineering Center in Maintaining Widely Used Hydrologic and Water Resource Computer Models
TP-19	Suspended Sediment Discharge in Streams	TP-57	Flood Damage Assessments Using Spatial Data Management Techniques
TP-20	Computer Determination of Flow Through Bridges	TP-58	A Model for Evaluating Runoff-Quality in Metropolitan Master Planning
TP-21	An Approach to Reservoir Temperature Analysis	TP-59	Testing of Several Runoff Models on an Urban Watershed
TP-22	A Finite Difference Methods of Analyzing Liquid Flow in Variably Saturated Porous Media	TP-60	Operational Simulation of a Reservoir System with Pumped Storage
TP-23	Uses of Simulation in River Basin Planning	TP-61	Technical Factors in Small Hydropower Planning
TP-24	Hydroelectric Power Analysis in Reservoir Systems	TP-62	Flood Hydrograph and Peak Flow Frequency Analysis
TP-25	Status of Water Resource System Analysis	TP-63	HEC Contribution to Reservoir System Operation
TP-26	System Relationships for Panama Canal Water Supply	TP-64	Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study
TP-27	System Analysis of the Panama Canal Water Supply	TP-65	Feasibility Analysis in Small Hydropower Planning
TP-28	Digital Simulation of an Existing Water Resources System	TP-66	Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems
TP-29	Computer Application in Continuing Education	TP-67	Hydrologic Land Use Classification Using LANDSAT
TP-30	Drought Severity and Water Supply Dependability	TP-68	Interactive Nonstructural Flood-Control Planning
TP-31	Development of System Operation Rules for an Existing System by Simulation	TP-69	Critical Water Surface by Minimum Specific Energy Using the Parabolic Method
TP-32	Alternative Approaches to Water Resources System Simulation		
TP-33	System Simulation of Integrated Use of Hydroelectric and Thermal Power Generation		
TP-34	Optimizing flood Control Allocation for a Multipurpose Reservoir		
TP-35	Computer Models for Rainfall-Runoff and River Hydraulic Analysis		
TP-36	Evaluation of Drought Effects at Lake Atitlan		
TP-37	Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes		
TP-38	Water Quality Evaluation of Aquatic Systems		

- TP-70 Corps of Engineers Experience with Automatic Calibration of a Precipitation-Runoff Model
- TP-71 Determination of Land Use from Satellite Imagery for Input to Hydrologic Models
- TP-72 Application of the Finite Element Method to Vertically Stratified Hydrodynamic Flow and Water Quality
- TP-73 Flood Mitigation Planning Using HEC-SAM
- TP-74 Hydrographs by Single Linear Reservoir Model
- TP-75 HEC Activities in Reservoir Analysis
- TP-76 Institutional Support of Water Resource Models
- TP-77 Investigation of Soil Conservation Service Urban Hydrology Techniques
- TP-78 Potential for Increasing the Output of Existing Hydroelectric Plants
- TP-79 Potential Energy and Capacity Gains from Flood Control Storage Reallocation at Existing U.S. Hydropower Reservoirs
- TP-80 Use of Non-Sequential Techniques in the Analysis of Power Potential at Storage Projects
- TP-81 Data Management Systems of Water Resources Planning
- TP-82 The New HEC-1 Flood Hydrograph Package
- TP-83 River and Reservoir Systems Water Quality Modeling Capability
- TP-84 Generalized Real-Time Flood Control System Model
- TP-85 Operation Policy Analysis: Sam Rayburn Reservoir
- TP-86 Training the Practitioner: The Hydrologic Engineering Center Program
- TP-87 Documentation Needs for Water Resources Models
- TP-88 Reservoir System Regulation for Water Quality Control
- TP-89 A Software System to Aid in Making Real-Time Water Control Decisions
- TP-90 Calibration, Verification and Application of a Two-Dimensional Flow Model
- TP-91 HEC Software Development and Support
- TP-92 Hydrologic Engineering Center Planning Models
- TP-93 Flood Routing Through a Flat, Complex Flood Plain Using a One-Dimensional Unsteady Flow Computer Program
- TP-94 Dredged-Material Disposal Management Model
- TP-95 Infiltration and Soil Moisture Redistribution in HEC-1
- TP-96 The Hydrologic Engineering Center Experience in Nonstructural Planning
- TP-97 Prediction of the Effects of a Flood Control Project on a Meandering Stream
- TP-98 Evolution in Computer Programs Causes Evolution in Training Needs: The Hydrologic Engineering Center Experience
- TP-99 Reservoir System Analysis for Water Quality
- TP-100 Probable Maximum Flood Estimation - Eastern United States
- TP-101 Use of Computer Program HEC-5 for Water Supply Analysis
- TP-102 Role of Calibration in the Application of HEC-6
- TP-103 Engineering and Economic Considerations in Formulating
- TP-104 Modeling Water Resources Systems for Water Quality
- TP-105 Use of a Two-Dimensional Flow Model to Quantify Aquatic Habitat
- TP-106 Flood-Runoff Forecasting with HEC-1F
- TP-107 Dredged-Material Disposal System Capacity Expansion
- TP-108 Role of Small Computers in Two-Dimensional Flow Modeling
- TP-109 One-Dimensional Model for Mud Flows
- TP-110 Subdivision Froude Number
- TP-111 HEC-5Q: System Water Quality Modeling
- TP-112 New Developments in HEC Programs for Flood Control
- TP-113 Modeling and Managing Water Resource Systems for Water Quality
- TP-114 Accuracy of Computer Water Surface Profiles - Executive Summary
- TP-115 Application of Spatial-Data Management Techniques in Corps Planning
- TP-116 The HEC's Activities in Watershed Modeling
- TP-117 HEC-1 and HEC-2 Applications on the Microcomputer
- TP-118 Real-Time Snow Simulation Model for the Monongahela River Basin
- TP-119 Multi-Purpose, Multi-Reservoir Simulation on a PC
- TP-120 Technology Transfer of Corps' Hydrologic Models
- TP-121 Development, Calibration and Application of Runoff Forecasting Models for the Allegheny River Basin
- TP-122 The Estimation of Rainfall for Flood Forecasting Using Radar and Rain Gage Data
- TP-123 Developing and Managing a Comprehensive Reservoir Analysis Model
- TP-124 Review of U.S. Army corps of Engineering Involvement With Alluvial Fan Flooding Problems
- TP-125 An Integrated Software Package for Flood Damage Analysis
- TP-126 The Value and Depreciation of Existing Facilities: The Case of Reservoirs
- TP-127 Floodplain-Management Plan Enumeration
- TP-128 Two-Dimensional Floodplain Modeling
- TP-129 Status and New Capabilities of Computer Program HEC-6: "Scour and Deposition in Rivers and Reservoirs"
- TP-130 Estimating Sediment Delivery and Yield on Alluvial Fans
- TP-131 Hydrologic Aspects of Flood Warning - Preparedness Programs
- TP-132 Twenty-five Years of Developing, Distributing, and Supporting Hydrologic Engineering Computer Programs
- TP-133 Predicting Deposition Patterns in Small Basins
- TP-134 Annual Extreme Lake Elevations by Total Probability Theorem
- TP-135 A Muskingum-Cunge Channel Flow Routing Method for Drainage Networks
- TP-136 Prescriptive Reservoir System Analysis Model - Missouri River System Application
- TP-137 A Generalized Simulation Model for Reservoir System Analysis
- TP-138 The HEC NexGen Software Development Project
- TP-139 Issues for Applications Developers
- TP-140 HEC-2 Water Surface Profiles Program
- TP-141 HEC Models for Urban Hydrologic Analysis

- TP-142 Systems Analysis Applications at the Hydrologic Engineering Center
- TP-143 Runoff Prediction Uncertainty for Ungauged Agricultural Watersheds
- TP-144 Review of GIS Applications in Hydrologic Modeling
- TP-145 Application of Rainfall-Runoff Simulation for Flood Forecasting
- TP-146 Application of the HEC Prescriptive Reservoir Model in the Columbia River Systems
- TP-147 HEC River Analysis System (HEC-RAS)
- TP-148 HEC-6: Reservoir Sediment Control Applications
- TP-149 The Hydrologic Modeling System (HEC-HMS): Design and Development Issues
- TP-150 The HEC Hydrologic Modeling System
- TP-151 Bridge Hydraulic Analysis with HEC-RAS
- TP-152 Use of Land Surface Erosion Techniques with Stream Channel Sediment Models
- TP-153 Risk-Based Analysis for Corps Flood Project Studies - A Status Report
- TP-154 Modeling Water-Resource Systems for Water Quality Management
- TP-155 Runoff simulation Using Radar Rainfall Data
- TP-156 Status of HEC Next Generation Software Development
- TP-157 Unsteady Flow Model for Forecasting Missouri and Mississippi Rivers
- TP-158 Corps Water Management System (CWMS)
- TP-159 Some History and Hydrology of the Panama Canal
- TP-160 Application of Risk-Based Analysis to Planning Reservoir and Levee Flood Damage Reduction Systems
- TP-161 Corps Water Management System - Capabilities and Implementation Status

